



CLT 140

CMT 270

CHT 460

BATTERY HANDTOOL
PLASTIC STRAP

 **Cyklop®**

CLT 140 - The ideal entry into manual strapping.

The Cyklop CLT 140 Strapping Tool is perfectly suited for light applications with 9-13 mm strap and offers an excellent solution for manual strapping. It enables flexible operation and is particularly suitable for sensitive packages that require precision and care.



CMT 270 - The most versatile for medium-sized packages.

The Cyklop CMT 270 battery-powered hand tool is the ideal solution for tensioning, sealing, and cutting PET or PP strap. It combines all three functions in one device, making it perfect for universal applications, especially with medium-sized packages. The versatile application with 12 to 16 mm strap enhances your productivity and ensures efficient and reliable strapping with a tensioning force of up to 2500 Newtons.



CHT 460 - The strongest handtool device for secure strapping.

The CHT 460 battery-powered plastic strapping tool is the most powerful of its kind and is especially suitable for strapping PP and PET strap with a width of 15-19 mm. With an impressive tensioning force of up to 4500 N, it provides a secure hold even with heavy loads.



EASY TO USE

- ✓ Full Touch Display
- ✓ Favorite mode, display lock
- ✓ Strap alignment indicator
- ✓ Welding time settings
- ✓ Tension force settings

IMPROVED PERFORMANCE

- ✓ Variable tension speed
- ✓ Inching operation for tension
- ✓ Tension indicator (filled out bars)
- ✓ More cycles per charge

FLEXIBLE & RELIABLE

- ✓ Save favorite settings
- ✓ For PP/PET strap
- ✓ For heavy and light packaged goods
- ✓ Color display & audible signal
- ✓ Impact, dust, and moisture resistant

ACCESSORIES

- ✓ Protective cover for control panel
- ✓ Protective plate for rough surfaces



- ✓ Suspension bow for static locations



- ✓ Battery / Charger Bosch Li-Ion 18V, 4.0 Ah



TECHNICAL DATA	CLT 140	CMT 270	CHT 460
Strap width	9 - 13 mm	12 - 16 mm	15 - 19 mm
Strap thickness	PET: 0.40 - 0.80 mm PP: 0.50 - 0.80 mm	0.50 - 1.00 mm	0.80 - 1.30 mm
Tension force	150 - 1200 N	400 - 2500 N	400 - 4500 N
Tension speed	0 - 180 mm/s (7.0 in/s)	0 - 220 mm/s (8.6 in/s)	0 - 150 mm/s (5.9 in/s)
Weight with battery	3.8 kg	4.0 kg	4.2 kg
Dimensions mm	L 367 x W 149 x H 135	L 367 x W 149 x H 135	L 367 x W 152 x H 138
Battery / Charger	Bosch Li-Ion 18V, 4.0 Ah	Bosch Li-Ion 18V, 4.0 Ah	Bosch Li-Ion 18V, 4.0 Ah
Strappings per charge	600 - 1000	400 - 800	300 - 800